



AGGREGATE & EMULSION SPRAY SEAL UNIT

Designed for spraying emulsion & spreading aggregates simultaneously in one pass or in separate operations



Aggregate Spreader Facilities as Follows;

- The Aggregate spreader can spread aggregate up to 14mm in size.
- Cabin controlled or from the rear of the body.
- The feed of the material to the spreader box is maintained by the automatic control system.
- 2400mm spreading width available.
- 4 off 600mm wide doors or more available.
- Two pneumatic cylinders operate all 4 or more doors.
- 2 Split hydraulic augers are installed to help spread the material to full width, if required.
- Augers are controlled by limit switches, which can work independently.

Spray Bar Facilities as Follows;

- 150mm spacing 15 nozzle spray bar, used with aggregates independent operation or cabin electric/air independent controlled nozzles.
- Calibrated spray bar rates up to 2.0 litres per m2.
- Spray bar height is adjustable.
- Spray bar cleaning facility.
- Air or emulsion pumping systems.



Need service or spare parts on your existing Flocon products?

Our qualified service or spare parts technicians can help

Phone: (03) 9703 2891



Contact Rory Knight at Flocon for more information

Phone: (03) 9703 2777 Fax: (03) 9703 2933

Email: rory@flocon.com.au

Victoria, New South Wales, Queensland, South Australia, Western Australia & Tasmania

Product Information