





FLOCON ENGINEERING P/L
www.flocon.com.au

FULLY AUTOMATED PAVER MAINTENANCE UNIT

Designed for the use with hotmix & premix asphalts to
repair major road failures or pave new footpaths

Facilities as Follows;

- Up to 2.4mt wide models available.
- The spread width is adjustable from 0.5mts to 2.4mts, left to right and full width spreads.
- Spreading angle is adjustable left to right from 10 – 150mm.
- Depth of spread is adjustable from 10 - 150mm.
- Leveling wheels on the paver adjustable up to 3.0 mts.
- Fully cabin controlled automatic feeding of paver via an Ultrasonic sensor operating the conveyor system.
- Rear discharge and side conveyor discharge are externally hand remote radio controlled.
- Twin pressure adjustable air cylinders, forcing the Paver onto the road surface.
- A adjustable guide pole is located at the front of the vehicle.
- Left and right hydraulically operated augers available.
- Hydraulically operated raise & lower safety winch system.
- 2.0 kph vehicle ground speed may be required to spread at 2.4mt widths.
- Auxiliary vehicle transmission available. Low gear ratio 2.30:1.



Product Information

Need service or spare parts on your existing Flocon products?

Our qualified service or spare parts technicians can help

Contact our staff at Flocon for more information

Phone: (03) 9703 2777

Email: reception@flocon.com.au

Flocon Engineering Pty Ltd is Nationwide